

# Juice Encoder


EN 5004 - 4 in 1 MPEG-4 AVC/H.264 HD Encoder



**The Juice Encoder EN 5004** - 4 in 1 MPEG-4 AVC/H.264 HD encoder is a professional HD audio & video encoding and multiplexing device with powerful functionality. It has 4 channels HDMI (or SDI) input interfaces, supporting MPEG4 AVC/H.264 High Profile code format. This device can simultaneously encode 4 channel HD programs; moreover, it has an ASI input and can multiplex the input TS with the 4 encoded program to generate ASI and IP output. Also, the PSI/SI information can be inserted into MPTS output. In conclusion, its high integrated and cost effective design makes the device widely used in varieties of digital distribution systems.

## Key Features

- Support AVC/H.264 High Profile Level 4.0 video encoding, Advanced video pretreatment algorithm
- Support MPEG1 Layer 2, HE-AAC (V2) or LC-AAC audio encoding (optional)
- 4 channel HDMI (or SDI) inputs and 1 ASI input with Mux
- Support PSI/SI editing and inserting
- Support VBR or CBR video bitrate mode
- Support 720P, 1080I, 1080P HD video format
- Support ASI output MPTS or 4 SPTS
- Support IP output (UDP) MPTS and 4 channel SPTS, unicast/multicast
- Support IP null packet filter
- Support PID filter and transparent transport.
- Real-time effective output bit-rate monitoring
- Support update device through NMS port
- Support LCD / keyboard operating, and network management (SNMP)



## INPUT

4x SDI input> EN5004-SDI  
4x HDMI input>EN5004-HDMI  
1xASI input, BNC interface

## VIDEO

Resolution: 1920\*1080\_59.94P, 1920\*1080\_50P  
1920x1080\_59.94i, 1920x1080\_50i  
1280x720\_59.94p, 1280x720\_50p  
720x576\_50i, 720x480\_59.94i

Encoding: MPEG4 AVC/H.264 High Profile Level 4.0  
Bit-rate: 0.8Mbps~19Mbps (each channel)  
Rate Control: CBR, VBR  
GOP Structure: IBBP  
Advanced Pretreatment: De-interlacing, noise reduction, sharpening



## AUDIO

Encoding: MPEG-1 Layer 2, HE-AAC(V2), LC-AAC  
Sampling rate: 48KHz  
Resolution: 24-bit  
Bit-rate: 64Kb/s~384Kb/s each channel

## MULTIPLEXING

1xASI input multiplexed and 4 encoding channel SPTS

## STREAM OUTPUT

2xASI outputs, BNC interface  
MPTS and 4 SPTS over UDP,10/100Base-T Ethernet interface, support unicast / multicast

## SYSTEM FUNCTION

LCD/keyboard operating, net manager (SNMP)Chinese-English control interface  
Ethernet software upgrade

## INTERFACES ON REAR PANEL

Dimension (W× L× H): 440mm×410mm×44.5mm  
Approx weight: 4kg  
Temperature: 0~45 °C (work), -20~80 °C (Storage)  
Power: AC 100V-220V±10%, 50/60Hz  
Consumption: 25W

Košice / Colorado / Moscow / Hong Kong / Shen-Zen / Singapore

Antik Technology  
Global Office  
Carskeho 10, 04001 Kosice, Slovakia (European Union)  
Tel.: +421 55 30 12345 / Fax: +421 55 623 4401 / E-mail: info@antiktech.com / Skype: juiceiptv

**ADVANCE INFORMATION:**  
This document contains the specification for a product under continuous development. Specifications may change in any manner without notice. Visit [www.antiktech.com](http://www.antiktech.com) for updates.  
Some of the technologies mentioned in this document can be licensed by third parties.  
License Agreement in such cases must be obtained separately.

