

Juice Encoder


EN 5008



The Juice Encoder EN 5008 8-in-1 MPEG-4 AVC/H.264 HD encoder is our newest professional HD audio & video encoding and multiplexing device with powerful functionality. It is equipped with 8 HDMI channels input supporting MPEG-4 AVC/H.264 High Profile code format & main Profile code format and 1 ASI input. It can multiplex the ASI input TS and the 8 encoded SPTS to generate a MPTS output with the inserted PSI/SI information. In conclusion, its high integration and cost-effective design make this device widely used in variety of digital distribution systems such as CATV digital head-end, satellite and terrestrial digital TV, etc.

Key Features

- Support 8 HDMI channels input & 1 ASI Input
- Support H.264/AVC high profile level 4.0 video encoding
- Support MPEG1 Layer 2 (HE-AAC (V2), LC-AAC optional) audio encoding
- Support PSI/SI editing and inserting
- Support VBR/CBR video bitrate mode
- Support 720P, 1080I, 1080P HD video format
- Support ASI output MPTS or 8 SPTS
- Support IP Output MPTS and 8 SPTS
- Support IP null packet filter
- Real-time output bit-rate monitoring
- Update device through NMS port
- Support LCD / keyboard operating, and network management (SNMP)



INPUT

8×HDMI inputs
1 ASI input, BNC interface

VIDEO

Resolution: 1920×1080_60P, 1920×1080_50P
1920×1080_60i, 1920×1080_50i
1280×720_60P, 1280×720_50P
720×576_50i, 720×480_60i

Encoding: MPEG-4 AVC/H.264
Bit-rate: 0.8Mbps~19Mbps (each channel)
Rate Control: CBR/VBR
IBBP: GOP Structure
Advanced Pretreatment: De-interlacing, Noise Reduction, Sharpening



AUDIO

Encoding: MPEG-1 Layer 2, HE-AAC (V2), LC-AAC
Sampling rate: 48KHz
Bit-rate: 64Kbps~384Kbps each channel

MULTIPLEXING

1 ASI input multiplexed with local 8 channels of TS

STREAM OUTPUT

2*ASI output, BNC interface
MPTS and 8 SPTS over UDP, 1000 Base-T Ethernet interface (UDP unicast / multicast);

SYSTEM FUNCTION

LCD/keyboard operating, net manager (SNMP)
English control interface
Ethernet software & hardware upgrade

INTERFACES ON REAR PANEL

Dimension (W×L×H): 440mm×410mm×44.5mm
Approx weight: 4kg
Temperature: 0~45 °C (work), -20~80 °C (Storage)
Power: AC 100V-220V±10%, 50/60Hz
Consumption: 25W

Košice / Colorado / Moscow / Hong Kong / Shen-Zen / Singapore

Antik Technology
Global Office
Carskeho 10, 04001 Kosice, Slovakia (European Union)
Tel.: +421 55 30 12345 / Fax: +421 55 623 4401 / E-mail: info@antiktech.com / Skype: juiceiptv

ADVANCE INFORMATION:
This document contains the specification for a product under continuous development. Specifications may change in any manner without notice. Visit www.antiktech.com for updates.
Some of the technologies mentioned in this document can be licensed by third parties.
License Agreement in such cases must be obtained separately.

