ANTIK

Digital Signage Solution



ANTIK Digital Signage Solution

Comprehensive Multimedia Advertising Delivery System







Kev Features

- complex advertising delivery system
- combination of live TV streams with standard multimedia designing components available
- large variety of indoor & outdoor LED TV panels
- low power consumption
- HD & Full HD resolution
- low operational costs

TV and many years in IPTV, we created low-investment and low operational costs LED panel system controlled by state-of-art ANTIK DS Management System. You can either upload ready to publish campaign delivered by your advertising clients or build your own campaign. To design the campaign, all standard multimedia components can be used – pictures, music, video (even in combination with live TV channel broadcasting) all mixed with many eye-catching effects.

TV panels itself are controlled by low-power Antik DS settop boxes. In comparison to Intel PC based panels, in each project you save significant investment money, not mentioning dramatically lower power consumption and quiet operation (no fan on set-top box necessary).

Antik Mini 2

Set-Top Box for Digital Signage



Inputs / Outputs

- DVB-C/T/T2/S2/ISDB-T Tuner Input (optional)
- HDMI 1.4
- TOSLINK Digital Audio Interface
- CVBS (3,5 mm jack for SCART/RCA cable connection)
- 1x USB 2.0

- 1x, 2x, 4x RJ45 (Ethernet 10/100 base Tx or 10/100/1000 base Tx)
- infrared receiver
- Embedded WiFi 802.11n (optional)
- external IR input

Highlights

- Full HD (1080p) video support
- Interactive TV support
 - multicast TV
- EPG, VOD, Mosaic

- Segment streaming and buffering for OTT delivery even in low-speed networks
- Hybrid broadcast-broadband TV support
- Intelligent low power consumption management







Minimal HW specification for DSS Management server

CPU: Intel Core i5

RAM: 4 GB

HDD: 1x100 GB SATA Ethernet: 100 Mbit

OS: Linux Debian 8 64 bit

Totem 55" vertical

ADS1055V



Energy protection class:

Typical power consumption:

Screen size: Resolution:

Technology:

Inputs:

Weight:

Dimensions:

A+

250 W (in operation), 0,3 W (standby)

139 cm (55")

Full HD (1920×1080)

LED

HDMI, CVBS, DVI, TOSLINK

95 kg

2040x960x350 mm

Totem 42" vertical

ADS1042V



Energy protection class:

Typical power consumption:

Screen size:

Resolution:

Technology:

Inputs:

Weight:

Dimensions:

А

240 W (in operation), 0,3 W (standby)

106 cm (42")

Full HD (1920×1080)

LED

HDMI, CVBS, DVI, TOSLINK

70 kg

2005x805x350 mm

Wall-mount 42" horizontal panel

ADS1042H



Energy protection class:

Typical power consumption:

Screen size:

Resolution:

Technology:

Inputs:

Weight:

Dimensions:

A+

240 W (in operation), 0,3 W (standby)

106 cm (42")

Full HD (1920×1080)

LED

HDMI, CVBS, DVI, TOSLINK

38 kg

1075x668x150 mm

6 www.antiktech.com

Wall-mount 19" horizontal panel

ADS1019H



Energy protection class:

Typical power consumption:

Screen size:

Resolution:

Technology:

Inputs: Weight:

Dimensions:

А

35 W (in operation), 0,3 W (standby)

48 cm (19")

Full HD (1920×1080)

LED

HDMI, CVBS, DVI, TOSLINK

11 kg

467x315x42 mm

Leaflet holder 26" vertical

ADS1026V



Energy protection class:

Typical power consumption:

Screen size:

Resolution:

Technology:

Inputs:

Weight:

Dimensions:

А

65 W (in operation), 0,3 W (standby)

66 cm (26")

Full HD (1920×1080)

LED

HDMI, CVBS, DVI, TOSLINK

50 kg

1850x750x610 mm

8 www.antiktech.com

ANTIK Event navigation system

